

1

INTRODUCTION

This book aims to provide a guide to the description of sedimentary rocks in the field. It explains how to recognise the common lithologies, textures and sedimentary structures, and how to record and measure these features. There is a chapter explaining how fossils can be studied in the field, since they are common in many sedimentary rocks and are very useful for palaeoenvironmental analysis. A concluding chapter gives a brief introduction to the interpretation of sedimentary rock successions: facies, facies associations, cyclic sediments and sequences.

1.1 Tools of the Trade

Apart from a notebook (popular size around 20×10 cm), pens, pencils, appropriate clothing, footwear and a rucksack, the basic equipment of a field geologist comprises a hammer, chisel, hand-lens, compass-clinometer, tape measure, acid bottle, sample bags and marker pen. A GPS receiver is most useful, and not only in remote areas (see Section 1.3). A hard hat for protection when working below cliffs and in quarries, and safety goggles for the protection of the eyes while hammering, should also be taken into the field and used; see Section 1.4 for further safety considerations. A camera, plus spare film or memory, is invaluable. Topographic and geological maps should also be carried, as well as any pertinent literature. If a lot of graphic logging is anticipated (see Section 2.4) then pre-prepared sheets can be taken into the field. Non-geological items which are useful and can be carried in a rucksack include a whistle, first-aid equipment, matches, emergency rations, knife, waterproof clothing and a 'space blanket'.

For most sedimentary rocks, a geological hammer of around 0.5–1 kg (1–2 lb) is sufficiently heavy. However, do be sympathetic to the outcrop and remember that many future generations of geologists will want to look at the exposure. In many cases it will not be necessary to hammer, since it will be possible to collect loose fresh pieces from the ground. A range of chisels can be useful if a lot of collecting is anticipated.

A *hand-lens* is an essential piece of equipment; $\times 10$ magnification is recommended since then grains and features down to 100 microns across can be observed. Holding the lens close to your eye, the field of view being

examined with a $\times 10$ lens is about 10 mm in diameter. To become familiar with the size of grains as seen through a hand-lens, examine the grains against a ruler graduated in millimetres. For limestones, it can be easier to see the grains after licking the freshly broken surface.

A compass-clinometer is important for taking routine dip and strike and other structural measurements, but also for measuring palaeocurrent directions. Do not forget to correct the compass for the angle between magnetic north and true north. This angle of declination is normally given on topographic maps of the region. You should also be aware that power lines, pylons, metal objects (such as your hammer) and some rocks (although generally mafic–ultramafic igneous bodies) can affect the compass reading and produce spurious results. A tape or steel rule, preferably several metres in length, is necessary for measuring the thickness of beds and dimensions of sedimentary structures. A metre-long staff with graduations can be useful for graphic logging. A compass usually has a millimetre–centimetre scale which can be useful for measuring the size of small objects such as pebbles and fossils.

For the identification of calcareous sediments a plastic bottle of hydrochloric acid (around 10%) is useful, and if some Alizarin red S is added, then dolomites can be distinguished from limestones (limestones stain pink, dolomites do not stain). Polythene or cloth bags for samples and a marker pen (preferably with waterproof, quick-drying ink) for writing numbers on the specimens are also necessary. Friable specimens and fossils should be carefully wrapped to prevent breakage.

For *modern sediments* and *unconsolidated rocks* you will need a trowel and/or spade. A length (0.5–1.5 metres) of clear plastic pipe, 5–10 cm in diameter, is very useful for pushing into modern sediments to obtain a crude core. Epoxy-resin cloth peels can be made in the field of vertical sections through soft sandy sediments. The techniques for taking such peels are given in Bouma (1969). In essence, cut and trim a flat vertical surface through the sediments; spray the resin on to the cut surface; place a sheet of muslin or cotton against the sediments and then spray the cloth. Leave for the resin to set (~ 10 minutes) and then carefully remove the cloth. A thin layer of sediment should be glued to the cloth and will show the various structures. Lightly brush or shake off excess, unglued sediment. Modern beach, dune, river, tidal flat and desert sediments are ideal for treatment in this way. Fibreglass foam (although a hazardous substance) can also be sprayed on to loose sediment to take a sample.

1.2 Other Tools for the Field

More sophisticated instruments are taken into the field on occasion to measure a particular attribute of sedimentary rocks. Normally these are used as part

of a more detailed and focused research effort, rather than during a routine sedimentological study. Such tools include the mini-permeameter, magnetic susceptibility recorder (kappameter), gamma-ray spectrometer and ground-penetrating radar equipment.

The mini-permeameter is a tool for estimating the permeability of a rock and portable ones are available for use in the field.

The magnetic susceptibility ('mag-sus') of sedimentary rocks can be measured relatively easily in the field, although in many it is very weak. Mudrocks and others with high organic matter contents and iron minerals tend to give higher readings. With measurements taken every few centimetres or so, a mag-sus stratigraphy can be produced; from this, cycles and rhythms can be recognised, especially in basinal facies.

Gamma-ray spectrometry is a technique for measuring the natural gamma radiation emitted from rocks; it can be used to determine the amount of clay in a succession and so is useful for distinguishing different types of mudrock, or the variation in clay content of muddy sandstones and limestones. Measurement of the gamma-ray spectrum in the field with a portable spectrometer has been used to correlate surface outcrops with each other and with the subsurface.

Ground-penetrating radar is a useful technique for looking at the structure and variation of shallow subsurface sediments, as in modern floodplains and coastal plains. Sedimentary units, such as point-bar sands and oxbow lake fills, can be recognised beneath the surface.

1.3 Use of GPS in Sedimentary Studies

The GPS (global positioning system) is becoming a standard instrument to take into the field for determining location, but it can also be used for measuring sedimentary sections. GPS provides a very precise location of where you are and this reading of latitude and longitude (or grid reference) can be entered in your field notebook and on logging sheets. The receiver also enables you to travel from one place to another or to find a specified location, or to back-track from whence you came. The accuracy of the reading from the receiver depends on several factors (make and model, time at location, design, corrections, etc.) and the method of positioning. With autonomous GPS the precision is 5–30 metres; using differential GPS (DGPS) and applying corrections, accuracy can be less than 3 metres. However, a reference station does have to be set up for DGPS.

GPS receivers now have a good memory so that all readings from the day, indeed the week, can be recalled, enabling you to retrace your steps and visit the precise localities again with no difficulty. This is immensely useful in landscapes where there are no distinctive features. Data from the receiver

can of course be downloaded directly to a PC so that a permanent record is kept of where you went.

Apart from the advantage of knowing where you are, GPS does have the potential to enable you to measure medium to large structures with a better degree of accuracy than with using just a map and tape measure. With channel-fills, reef bodies, conglomeratic lenses, etc., several hundred metres across or more, taking several GPS measurements will enable a better estimate of dimensions to be obtained.

1.4 Safety in the Field and General Guidance for Fieldwork

Working in the field should be a safe, enjoyable and very rewarding experience, as long as a few basic and sensible precautions are taken. Geological fieldwork is an activity involving some inherent risks and hazards, such as in coastal exposures, quarries, mines, river sections and mountains. Severe weather conditions may also be encountered in any season, especially on mountains or at the coast. Fieldwork does involve an important element of self-reliance and the ability to cope alone or in a small group. You are responsible for your own safety in the field, but nevertheless there are some simple precautions you can take to avoid problems and minimise risks.

- Do wear adequate clothing and footwear for the type of weather and terrain likely to be encountered. Try to know the weather forecast for the area before you go out for the day. Keep a constant lookout for changes. Do not hesitate to turn back if the weather deteriorates.
- Walking boots with good soles are normally essential. Sports shoes are unsuitable for mountains, quarries and rough country.
- Plan work carefully, bearing in mind your experience and training, the nature of the terrain and the weather. Be careful not to overestimate what can be achieved.
- Learn the mountain safety and caving codes, and in particular know the effects of exposure. All geologists should take a course in First Aid.
- It is good practice before going into the field to leave a note and preferably a map showing expected location of study and route, and time of return.
- Know what to do in an emergency (e.g., accident, illness, bad weather, darkness). Know the international distress signal: six whistle blasts, torch flashes or waves of a light-coloured cloth, repeated at one-minute intervals.
- Carry at all times a small first-aid kit, some emergency food (chocolate, biscuits, mint cake, glucose tablets), a survival bag (or large plastic bag), a whistle, torch, map, compass and watch.
- Wear a safety helmet (preferably with a chin strap) when visiting old quarries, cliffs, scree slopes, etc., or wherever there is a risk from falling objects. It is obligatory to do so when visiting working quarries, mines and building sites.

INTRODUCTION

- Avoid hammering where possible; be a conservationist.
- Wear safety goggles (or safety glasses with plastic lenses) for protection against flying splinters when hammering rocks or using chisels.
- Do not use one geological hammer as a chisel and hammer it with another; use only a soft steel chisel.
- Avoid hammering near another person or looking towards another person hammering. Do not leave rock debris on the roadway or verges.
- Be conservation-minded and have a sympathetic regard for the countryside and great outdoors, and for the people, animals and plants that live there.
- When you are collecting specimens, do not strip or spoil sites where special fossils and rare minerals occur. Take only what you really need for further work.
- Take special care near the edges of cliffs and quarries, or any other steep or sheer faces, particularly in gusting winds.
- Ensure that rocks above are safe before venturing below. Quarries with rock faces loosened by explosives are especially dangerous.
- Avoid working under an unstable overhang.
- Avoid loosening rocks on steep slopes.
- Do not work directly above or below another person.
- Never roll rocks down slopes or over cliffs for amusement.
- Do not run down steep slopes.
- Beware of landslides and mudflows occurring on clay cliffs and in clay pits, or rockfalls from any cliffs.
- Avoid touching any machinery or equipment in quarries, mines or building sites. Comply with safety rules, blast warning procedures, and any instructions given by officials. Keep a sharp lookout for moving vehicles, etc. Beware of sludge lagoons.
- Do not climb cliffs, rock faces or crags, unless you are an experienced climber and have a partner.
- Take great care when walking or climbing over slippery rocks below the high-water mark on rocky shores. More accidents to geologists, including fatalities, occur along rocky shorelines than anywhere else.
- Beware of traffic when examining road cuttings.
- Railway cuttings and motorways are generally not open to geologists, unless special permission has been obtained from appropriate authorities.
- Do not enter old mine workings or cave systems unless experienced and properly equipped.
- Avoid getting trapped by the tide on intertidal banks or below sea-cliffs. Obtain local information about tides and currents. Pay particular attention to tidal range. For sea-cliffs, local advice can be obtained from HM Coastguards.
- Always try to obtain permission to enter private property.

