Create a Dreamweaver Site

reamweaver is a full-featured Web application development tool. Dreamweaver's features not only assist you with creating and editing Web pages, but also with managing and maintaining your entire Web site. To take advantage of all of Dreamweaver's Web development features, you need to set up a Dreamweaver site that defines your development environment and tells Dreamweaver where files are located.

A Dreamweaver site organizes your Web site to facilitate the development process. In most cases, you create and edit your Web pages in a folder on your local computer and

then, when your Web site is completed to your satisfaction, you copy the Web page files to the folder where visitors access your Web site. That is, you copy the Web page files to the folder located at the URL that users type to view your Web site. To support the development process, you create a Dreamweaver site with two different parts: the Local site and the Remote site.

The *Local site* is the folder where you store the files for your Web site while creating and editing them. People visiting your Web site cannot access the files in this site. The Local site is usually located on your own computer, but can be anywhere.

Create a Dreamweaver Site

The panel on the right may not appear, depending on whether it was set on or off

Note: See Chapter 2 to learn about the

Dreamweaver interface.

the last time Dreamweaver was closed. You

can open and close the panel by clicking the





3 Click New.4 Click Site.

Click Site.

2 Click Manage Sites.

side arrow.

chapter

The Site Definition dialog box appears, displaying the Local Info section of the Advanced tab.

- Click the Advanced tab if necessary.
- 5 Type a name for your new site.
- 6 Click the folder button (a) to browse to the folder where you want to store the Local site.



The navigation window opens.

Navigate to the folder where you want to store the Web site folders.

In this example, sites-local is selected.

- 8 Click the New Folder button (🗐).
- 9 Type a name for the new folder.
- 10 Click Open.

Dreamweaver opens the new folder.



Can I set up a Dreamweaver site for an existing Web site?

Yes. The process is basically the same for a new Web site or an existing Web site. During the setup, you enter a path to the Web site files. For a new Web site, the path points to a new empty directory; for an existing site, the path points to a directory that contains the existing Web site files.

How do I set up the Dreamweaver site for an existing site if the Web site files are currently located only at the Remote site?

You can set up a Local site and then copy the files into the Local site. Copy the entire folder structure from the Remote site into the Local site, not just the individual files, so that Dreamweaver does not upload files to the wrong location.

What is the Basic option for setting up a new Dreamweaver site?

The Basic option provides a wizard that prompts for information one step at a time. If you click the Basic tab at the top of the Site Definition window, Dreamweaver starts the wizard that guides you through the steps required to create a new site. This procedure is slower, but can be useful if you are new to developing Web sites.

Create a Dreamweaver Site (Continued)

he *Remote site* is the location where users can view your Web pages. After you have finished creating and editing your Web pages in your Local site, you move the completed files to the Remote site. Your Web site might be located in a specific folder on your company network, in a folder assigned to you by a Web hosting company, or in a folder on your own computer if you run your own Web server. If the Remote site is on a different computer than the Local site, the files are moved via File Transfer Protocol (FTP) or a local network that includes the Remote site. The Dreamweaver site organizes all the documents in your Web site. It tracks and maintains links, manages files, and handles the file transfers from your local site to your remote site. Your Local site and your Remote site need to contain the same hierarchical structure of folders to prevent Dreamweaver from copying files from the Local site into the wrong folder in the Remote site, and vice versa.

You can manage your files better if you create a folder on your computer (that is, a Local site) that contains all your Dreamweaver sites. Each site is stored in a folder named with the Dreamweaver site name.

Create a Dreamweaver Site (continued)

- You can create a folder to hold images, but Dreamweaver does not require one.
- 1 Click Select.

The Site Definition dialog box displays the path to the Local root folder.

- If you created a folder for your images, add its path/filename to Default images folder.
- Type the URL that you will use to view your Web pages.

In this example, the Local site is on a local computer, so localhost is used.

Sec.	a de com		
	M GBPB	*	
Cinages -			
		Colort	
Select DreamweaverBook		Cancel	
			State -

Site Definition for Dreamwe	averBook	×
Basic Advanced		
Busic Advenced Cologram Designed Design		
	CK Cancel	Halp

<u>ch</u>apter





How does Dreamweaver use a default images folder?

If you specify a default images folder during the Dreamweaver site setup, Dreamweaver places new images that you add to your site into that folder, unless you explicitly put the images elsewhere. For example, if you drag an image from the Desktop into the Document window, Dreamweaver places a copy of the image in the default folder.

Will the name that I give my site appear anywhere on my finished Web site?

No. The name is used only for keeping track of different sites in Dreamweaver. It appears in the Site drop-down list at the top of the Site window. It also appears in the Files panel, which is used to manage Web site files. Using the Files panel is discussed in Chapter 2.

Are Remote and Local the only possible sites in a Dreamweaver site?

No. An additional site — the Testing Server site — can be defined. You need this site only for dynamic Web sites that use ColdFusion, PHP, or another dynamic Web application language. This chapter does not discuss test sites because it does not discuss dynamic Web sites. Chapter 14, which discusses dynamic sites, explains how to set up a test site.

Change Dreamweaver Site Information

he site information (also called site settings) is the information you provided when you set up the site, such as the name of the Dreamweaver site, the path to the directory where the Web site files are stored, the URL to your Web site, the path to an images folder, information about the remote site, and so on. Dreamweaver stores this information in an internal file, with the information associated with the individual Dreamweaver site. Sometimes you discover that you provided incorrect information to Dreamweaver when you set up your Dreamweaver site. Or, you provided the correct information, but the information changed at a later time. You can change the information for your Dreamweaver site at any time.

Dreamweaver provides an option to edit the settings for a site. When you select the edit option, you can access the same dialog boxes that you used to enter the information when you set up the site. You can change any of the site settings and save the new settings for the Dreamweaver site.

Change Dreamweaver Site Information

- Open the Manage Sites dialog box.
- **Note:** See the section "Create a Dreamweaver Site" earlier in this chapter to open the Manage Sites dialog box.
- Click the site name.
 - This example uses a site named DreamweaverBook.
- 3 Click Edit.
 - The Local Info category appears active in the Site Definition dialog box.
- 4 Change any information you need to change.
- **Note:** To change information for the Remote site, click Remote Info and change the information in the Remote Info category.



anage Sites DreamweaverBook Examples Vatidentity	New Edt Duplcate Remove Export Import	3
Done te Definition for D	Help	
asic Advanced		
Category	Local Info	
Local Info Remote Info	Site name:	DreamweaverBook
Testing Server Cloaking		Ci)Documents and Settings(Janet)My Dor
Design Notes Site Map Layout File View Columns Contribute		<u>R</u> efresh local file list automatically
Contracto	Default images folder:	C:\Documents and Settings\Janet\My Dor
	Links relative to:	Document Site root
	HTTP address:	http://localhost/
		This address is used for site relative links, and for the Link Checker to detect HTTP links that refer to your own site
		Use case-sensitive link checking
	Cache:	Enable cache
		The cache maintains file and asset information in the site. This speeds up the Asset panel, link management, and Site Map features.

chapter

Remove a **Dreamweaver Site**

ou can remove a Dreamweaver site when you no longer need it. The settings saved for the site are deleted from Dreamweaver's internal files. When you remove a Dreamweaver site, Dreamweaver permanently deletes the site information. You cannot undo the action and recreate the site. The site is gone forever.

The Dreamweaver site refers only to the site information. The site contains a path to the root folder where the Web

site files are stored. When you remove the site, the path to the Web site files is deleted, along with all the site settings. However, the files themselves are not deleted; the folder with the files is untouched. You could create a new Dreamweaver site, with a new name, and give the new site the same root directory path that was set for the site you just removed. The new site would then display the same Web pages that were displayed by the site you removed.

Remove a Dreamweaver Site

 Open the Manage Sites dialog box. **Note:** See the section "Create a Dreamweaver Site" earlier in this chapter to open the Manage Sites dialog box 2 Click the name of the site you want removed. This example refers to the site DreamweaverBook.Copy. Click Remove. A window opens to verify that you want to delete the site. 4 Click Yes. Dreamweaver removes the site name from the list of sites. 5 Click Done.

	Manage Sites	×	
2	DreamweaverBook Examples NetIdentity	New Edit Duplicate Remove Export Import	3
	Done Manage Sites	Help	
5	DreamweaverBook DreamweaverBook copy Macromedia Dreamweaver Macromedia Dreamweaver Macromedia Dreamweaver Macromedia Dreamweaver Delete the selected s	action.	

Move a Dreamweaver Site

reamweaver stores information in internal files for each Dreamweaver site, such as the site name, the path to the root directory, the URL to the Web site, information needed to connect to the Remote site, and so on. In some cases, you might need to set up the same Dreamweaver site on a different computer. Perhaps you need to change your development environment to a different computer; or, if you need to work on the Web site in cooperation with other developers, your co-developers will need to establish the same Dreamweaver environment to coordinate your work. Rather than setting up a new Dreamweaver site on a new computer, with the extra work and potential errors, you can move the existing Dreamweaver site to another computer.

Moving a Dreamweaver site requires three steps: Exporting the current site, moving the file containing the site information to the new computer, and importing the site file into Dreamweaver on the new computer. When you export the current site, the site information is stored in a file called sitename.ste. The exported file contains the information in XML format in a text file that you can examine in a text editor. You move the exported file to the new computer and import it into Dreamweaver.

Move a Dreamweaver Site

Export the existing site

- 1 Open the Manage Sites dialog box.
- **Note:** See the section "Create a Dreamweaver Site" to open the Manage Sites dialog box.
- 2 Click the site name.
- 3 Click Export.

The Exporting dialog box appears.

- 4 Check an option if the default is not correct (○ changes to ○).
- 5 Click OK.

The export site navigation dialog box opens.

- 6 Click here and navigate to the folder where you want to store the exported site.
- **7** Click Save.

Dreamweaver saves the file with an .ste extension in the selected folder.



Save

Cancel

¥

My Compute

My Network

File name:

Save as type:

DreamweaverBook ste

Site definition files (".ste





Import on the new computer

the exported file is stored.

name in the Manage Sites box.

1 Click the filename.

12 Click Open.

9 Click Import.

8 Open the Manage Sites dialog box.

Are the Web site files automatically moved when you move the Dreamweaver site?

No. Only the site settings are included in the file that contains the exported site. One of the settings is the path to the root directory where the Web site files are stored.

You must move the actual Web site files separately. You can copy the files on the new computer into a folder with the same path, so that the current path is correct. Or, you can change the path to the root directory after you import the site, setting the path so that the Dreamweaver site looks for the Web site files in a different folder.

What does the file that contains the exported site look like?

The file contains the settings for the Dreamweaver site in XML format. The file begins with an XML tag, such as:

<?xml version="1.0" encoding="utf-8" ?>

Next, it starts each line of site information with a site tag, as follows:

<site>

The file then includes various settings. It includes information on the local site, starting with a tag resembling the following:

<localinfo sitename= "DreamweaverBook"

After the local site tag, the file contains a tag for the remote site, similar to the following:

<remoteinfo accesstype="ftp" host="janet.valade. com" ...

The file contains other tags containing other site settings.

Create a Web Page

fter you have set up your Dreamweaver site, you can create Web pages for the new Web site and store them in the local site. Dreamweaver provides a WYSIWYG (What You See Is What You Get) interface where you can add content to your Web page. You can see the content you enter and move or edit the page as desired. Dreamweaver also provides an interface where you can write HTML code directly if you prefer. The Dreamweaver interface is described in Chapter 2.

In this section, you create a simple Web page, using the WYSIWYG editor, to show the basic process. The next section shows how to save the Web page file in your Dreamweaver site.

A new blank page in Dreamweaver is not completely empty. It contains the required HTML tags, such as <head> and <body> tags, which do not display any content in the Web page.

Dreamweaver creates your Web page using code that conforms to the document type definition (DTD) specified for your Web page. The new document uses the DTD specified in your preference settings, but you can change it when creating a new document. Changing your preference settings is discussed in Chapter 2.

Create a Web Page

 Click File and choose New. Seneral Tomplates Basic page: 3 The New Document dialog box appears. Basic page ät BTML Dynamic pag HTML template Template page Other CSS Style Shoets Ubrary Ren Click Basic page. 2017 (Entire page) 2017 (Fragment) ActionScript CSS Fremesets Page Designs (CSS) <No previs 3 Click HTML. Starter Pages JavaCoript Page Designs 281 **Note:** The start page that displays when you open Dreamweaver provides the same menu Description HTML docum choices. 4 Click Create. Document Ture (DTD): SHTML 1.0 Transitional 4 Help Preferences... Get more of Create Cancel A new, blank Web page opens. 10 3 5. M. S. C. E. S. 🖸 Code 🔛 Split 🔄 Cesign Title: First Page 🚽 5 Type a title for the page. 0 0 0 0 0 0 × 5 0 0 0 6 This is my first Dreamweaver pace 6 Type the contents of the Web page. The filename is Untitled-1 because you have not yet saved the file and given it a name.

chapter

Save a Web Page

s with most other applications that create files, you must save the Web page or it will be lost when you exit Dreamweaver. Saving your Web page frequently as you work on it is always wise — that way, problems such as computer crashes cause as little content loss as possible. If you attempt to shut down Dreamweaver without saving a Web page, Dreamweaver prompts you to save it.

When you save the file, you give it a name. It is best to use only letters, numbers, hyphens, and underscores in the filename. Using punctuation, spaces, or special characters can sometimes cause problems with a Web server, making a file unviewable. Do not begin the filename with a number, which can also sometimes cause problems.

Most non-dynamic Web page filenames require the .htm or .html filename extension. If you are creating dynamic Web pages that interact with an application server and a database, you need to use an extension specific to the application, such as .cfm (ColdFusion), .jsp (Java server page), or .php. Chapter 14 discusses dynamic Web pages.

Save a Web Page

1 Click File and then choose Save As.

The Save As dialog box appears.

- 2 Click here to navigate to the local site.
- **3** Type a filename.
- 4 Click here and select the correct file type.
- 5 Click Save.
 - The filename tab now shows the filename.



Using Dreamweaver Page Designs

reamweaver comes with numerous predefined Web pages to help you create starter pages for a number of different types of sites. Using such ready-made designs can save you time and keep the pages within your site consistent.

Dreamweaver page-design documents are formatted and have placeholder information. When you select a page design, a Web page opens that is formatted and has placeholder content for the various parts of the Web page. You just need to replace the placeholder content with the content you want on your Web page. You can also change the Web page format until it suits you perfectly. Then, you save the document in the local site folder of your Dreamweaver site, giving it an appropriate filename.

The predefined pages are grouped into different categories, such as *Commerce* (display products and shopping carts), *Image* (formats for displaying images), *Text* (layouts for online newsletters and magazines), and *UI* (standard forms).

Page-design documents are not templates. They are just Web pages that have code already in them. You can edit the code as you need to and replace placeholder text and images. Templates are more complicated. Chapter 10 discusses the many uses and features of templates.

Using Dreamweaver Page Designs

1 Display the New Document dialog box.

- **Note:** See the section "Create a Web Page" to display the New Document dialog box.
- 2 Click Page Designs.

A list of available page designs appears.

- 3 Click page design.
 - Dreamweaver displays a preview and description of the design.
- 4 Click Create.

A new page opens with placeholder content.

- 6 Replace the placeholder information with the information you want on your Web page.
- Note: Chapter 3 discusses editing Web pages.
- **Note:** Chapter 3 discusses adding text and Chapter 5 discusses images.
- 6 Save the file.
- **Note:** See the section "Save a Web Page" to save a Web page.



PART I

Preview a Web Site

ou can view your Local site in a browser to see how it will look when published on your remote Web site. You can preview your Web pages at any time.

You can select a browser in which to preview the Web pages. The Preview in Browser menu item displays a list of browsers from which to choose. You can add or remove browsers from the list by changing your preference settings. Chapter 2 explains how to change preference settings. If you click Edit Browser List in the Preview in

Browser menu, the browser list preference settings are displayed for you to change.

You can create a list of up to 20 browsers that you can use to preview your Web pages. Unless you know exactly what browsers the visitors to your Web site will be using, you should test your Web pages in both current and older versions of the most popular browsers, including Internet Explorer, Firefox, and Netscape. This helps ensure that your Web site displays correctly for the widest possible range of users. You can set one of the browsers as the primary browser and one as the secondary browser.



Validate the Web Page

reamweaver provides a validation feature that checks the syntax of your code. The HTML syntax is validated based on the DTD you selected for your document. For example, if you chose XHTML 1.0 transitional for your DTD, the syntax is checked using that standard.

If you create your Web pages using Dreamweaver's WYSIWYG editor, Dreamweaver builds your source code and seldom makes syntax errors. However, if you edit the code yourself, or if you copied some Web page files into your Local site from a Web site that already exists, you need to validate the pages to be sure the syntax is correct. Dreamweaver displays the results of your validation in the bottom pane of your window in the Results panel. (Chapter 2 provides more details on using panels.) Each error is listed in a separate row, showing the line number in your source code that produced the error. An icon at the beginning of the line indicates the type of error.

The Web page, created earlier in this chapter, displaying the text "This is my first Dreamweaver page," and saved with the name FirstPage.html, is created by Dreamweaver and has no syntax errors. To show how the Validator works, the </head> tag and the </html> tag were removed from the source code.

Validate the Web Page

- 1 Click the Validate button (🖭).
- Click Validate Current Document.



 Validation results appear at the bottom in the Results panel.

chapter

Click the Split button (€ Macramatic Draamaaver 3 Beta 2 - [tAMyWebSiteChitectoralDraamaaveRook\FirstPage.html (04TML)] 👘 🗐 💌 Ma Edit + az. Iraat Koziy Tat Corranis Sta = rötü Hep
with line numbers.	
 The code window opens, showing the 	2 climit such as Therps //uma.all.org/1895/sheat10- 2 climit such as Therps //uma.all.org/1895/sheat10-
HTML source code.	4 cheta http-equiv/Context-TypeT centents/Test/Atals cheizets/so-0035-1" /s 5 child/First Pages/tills/
	13 6 まで、Catego を、CyChan to my Linet Decimenter page (内)の
	p dzbudyte 10
	This is any first Decamereever page
	(දේ) වි ද (20.55 ලෝක (1999 - 20.73 a)
	i ▼ Resulta Search Reference Validatori Targat Rowser Check Link Checker Size Reports FFF Log Server Debug — 5- 19-4 Filo Link Description
	O extra Click Application The test body? Since allowed within the off is only allowed within the Mark (2004) (2004) (2004) A extra Click Application The Test Test Residence and the Click Application (2004) The Test Test Residence and the Click Application (2004)
	A erflowk/FigPingentry 2 The "htm" top is missing an apport to give "PULS-Objectional] Company, Or note
Type on line 6 in the code window.	● Ana consulta Documentariae E Patric 2 - E ₁ - docuMD encourse and AuktOriaemana
Type <b html> on line 10.	(material)
	· · · · · · · · · · · · · · · · · · ·
Click P.	3 Gaudo
 New Validator results are displayed. 	4 St. 4 Chinteb Torsen Tage//stitleb
	2 Config-
	Critedap Critedap
	This is my first Desconsenser page
	(0) G_1 (0000 - −] 200 x 91 − 12/ 1 400
	Results Search Researce establish TerpelDisserCheck MilCheder She Reports TPP log TelverChebug Re Re Line Description
	Contraction of the second s
STER	C E servanorfield (1989) The end of servanize frank (2019). Little endered
STER A	C C revealed the Provide the

What types of information does the Validator display?

4 6

> The Validator displays three types of messages: 1) Informational messages just convey information and are not error messages; 2) warning messages point out incorrect syntax that is unlikely to affect the appearance of the Web page; and 3) error messages point out incorrect syntax that is very likely to affect the appearance of the Web page.

Each message is marked by an icon. The informational message icon looks like $\overline{\mathbf{Q}}$, the warning message icon looks like 🙆, and the error message icon looks like **9**.

Does the Web page need to be open before I can validate it?

No. You can validate any file. Click the filename in the Files panel. Next, click Windows, Results, and then click the Validation tab. If you have previously run a validation, the Validation Results panel will be open. To validate the selected file, you need to click the Validation button or the Run Validation button in the panel.

Can I validate more than one file at a time?

Yes, you can select more than one file in the Files panel, using Shift-click or Ctrl-click. Click Windows, Results, and the Validation tab. Or you can click the site name in the Files panel, then click Windows, Results, Validation tab, and all the files in the site will be validated.

Check Browser Compatibility

he HTML standards are set by the World Wide Web Consortium (W3C) (www.w3c.org). However, not all browsers and/or browser versions implement all parts of the standard the same way. In addition, some browsers have added HTML tags and attributes that are not in the standard and do not work in all browsers. Dreamweaver provides a feature that you can use to check which browsers support the HTML code in your Web page.

Dreamweaver stores a list of target browsers that it uses to check compatibility. You can add browsers to or remove browsers from the target browser list. If you know what browsers your visitors are likely to use, you can include only those browsers in the target browser list. If you do not know, make your code compatible with popular browsers. You can also select which version of the browser to include. For example, older browsers do not support (Cascading Styole Sheets).

The FirstPage Web page file created earlier in this chapter has no compatibility problems with the default set of target browsers. A problem arises, however, when an older version of IE (4.0) is added to the list of target browsers, as shown in the example in this section.

For the browser check feature to work as described, the Auto-check on Open feature must be turned on. To check that the feature is turned on, click and the feature is turned on, click the feature to turn should show a check by the feature. If not, click the feature to turn it on.

Check Browser Compatibility

Open a Web page.

Note: When the page is opened, Dreamweaver automatically checks for browser compatibility.

The green check mark means no browser compatibility problems.

2 Click 🖾 🔤 🛛 .

The Code Window opens.

3 Click I lick4 Click Settings.

A Die Arei, Dank Keit, Tale Carrent, Bie - Fried Heit The Ford Areit, Tale Carrent, Ford Areit, Bie Lab, Ball of Bie die die die die Areit, S. S The Ford Ford Heit - Start, The Second Ford Areit, S. S. S The Second Ford Heit - Second Ford Areit, S. S.
dock op Image: State and the second
Address
A the service set of the product of the set of the
Image: State of the second
<pre>decide active "Network" to acquiring " character active active Physics" / 0 decide active active The Physics active The Physics active active active Physics " / 0 decide active active The Physics active The Physics active The Physics active active active Physics " / 0 decide active active The Physics active The Physics active The Physics active active active Physics " / 0 decide active active The Physics active The Physics active The Physics active active active Physics active a</pre>
Image: State of the second
A change change change change from the property of the change of the from the property of the change of the cha
I control to a we first thereasoner parts (20) The is explicit. The is explicit. dedo-nor dedo-nor<
Image: State of the second
dodo os Autoremula Dramosove 1 field 2 - (, - lon dill resonance m Miller armesove field 2 - (, - lon dill resonance m M
dodo os Autoremula Dramosove 1 field 2 - (, - lon dill resonance m Miller armesove field 2 - (, - lon dill resonance m M
A Materimedia francessore & Efric 2 - [], - the dW manuscript in MM manuscript in MM final Days, build (VH fid) () A Materimedia francessore & Efric 2 - [], - the dW manuscript in MM manuscript in MM final Days, build (VH fid) () The time - L_2 II _ S col + [] (* 1 Li _ b) _ b = b = b = b = b = b = b = b = b = b
A Materimedia francessore & Efric 2 - [], - the dW manuscript in MM manuscript in MM final Days, build (VH fid) () A Materimedia francessore & Efric 2 - [], - the dW manuscript in MM manuscript in MM final Days, build (VH fid) () The time - L_2 II _ S col + [] (* 1 Li _ b) _ b = b = b = b = b = b = b = b = b = b
A Materimedia francessore & Efric 2 - [], - the dW manuscript in MM manuscript in MM final Days, build (VH fid) () A Materimedia francessore & Efric 2 - [], - the dW manuscript in MM manuscript in MM final Days, build (VH fid) () The time - L_2 II _ S col + [] (* 1 Li _ b) _ b = b = b = b = b = b = b = b = b = b
A Materimedia francessore & Efric 2 - [], - the dW manuscript in MM manuscript in MM final Days, build (VH fid) () A Materimedia francessore & Efric 2 - [], - the dW manuscript in MM manuscript in MM final Days, build (VH fid) () The time - L_2 II _ S col + [] (* 1 Li _ b) _ b = b = b = b = b = b = b = b = b = b
A Materimedia francessore & Efric 2 - [], - the dW manuscript in MM manuscript in MM final Days, build (VH fid) () A Materimedia francessore & Efric 2 - [], - the dW manuscript in MM manuscript in MM final Days, build (VH fid) () The time - L_2 II _ S col + [] (* 1 Li _ b) _ b = b = b = b = b = b = b = b = b = b
A Materimedia francessore & Efric 2 - [], - the dW manuscript in MM manuscript in MM final Days, build (VH fid) () A Materimedia francessore & Efric 2 - [], - the dW manuscript in MM manuscript in MM final Days, build (VH fid) () The time - L_2 II _ S col + [] (* 1 Li _ b) _ b = b = b = b = b = b = b = b = b = b
A Materimedia francessore & Efric 2 - [], - the dW manuscript in MM manuscript in MM final Days, build (VH fid) () A Materimedia francessore & Efric 2 - [], - the dW manuscript in MM manuscript in MM final Days, build (VH fid) () The time - L_2 II _ S col + [] (* 1 Li _ b) _ b = b = b = b = b = b = b = b = b = b
A Materimedia francessore & Efric 2 - [], - the dW manuscript in MM manuscript in MM final Days, build (VH fid) () A Materimedia francessore & Efric 2 - [], - the dW manuscript in MM manuscript in MM final Days, build (VH fid) () The time - L_2 II _ S col + [] (* 1 Li _ b) _ b = b = b = b = b = b = b = b = b = b
A data server lands Decommense E. Bets 2 + [:dis:dBracemenser BM/Bracemensere E.Bets 2 + [:dis:dBracemenser BM/Bracemensere Exactly (2011) * [2] M: Ell
the District Disc Disc Disc Disc Disc Disc Disc Disc
the District Disc Disc Disc Disc Disc Disc Disc Disc
The v V
Professor 11 P
Image: Solution of the soluti
Image: State of the state o
Image: Section 1
a construction of the second s
The is ery full Decomensary page.
Image: A start and a sequer function of the start and a sequer funct
detailofiers Pape/Latito detailofiers detail
The is erg feat Denomenance page.
The is explored for the second secon
dation The original Type of
dels as
debts as
Autorau December 1990

chapter

The Target Browsers dialog box opens.

- 5 Click the 🗹 by Microsoft Internet Explorer.
- 6 Click 4.0.
- 🕖 Click OK.

Dreamweaver now checks browser compatibility, including IE 4.0 as one of the target browsers.

in now shows incompatibility.

- A red line appears under the problem.
- 8 Click 🐼.

9 Click Show All Errors.

Dreamweaver lists the errors in the Reports panel in the bottom pane of the window.





What types of messages does Check Target Browsers display?

Check Target Browsers displays three types of messages: 1) Informational messages flag code that is not supported in a specific browser, but does not change the way the Web page displays; 2) warning messages point out code that will not display correctly in a specific browser, but will not cause any serious display problems; and 3) error messages flag code that may seriously affect the Web page appearance in a specific browser, such as making parts of the page disappear.

Each message is marked by an icon. The informational message icon looks like , the warning message icon looks like , and the error message icon looks like .

Does Dreamweaver check for syntax errors when it checks browser compatibility?

No. Dreamweaver checks only for HTML elements that are incompatible to any of the browsers in the Target Browser List. Elements that are not implemented in a specific browser are the only elements reported. To check for syntax errors, you need to use the Validator described in the previous section.

Publishing a Dreamweaver Site

he Web pages you create and edit in your Local site are not available to visitors to your Web site. To make your finished Web pages available on the World Wide Web (WWW), you need to publish your Dreamweaver site. Publishing your site means copying the Web page files to your Remote site.

When you set up your Dreamweaver site, you set up a Remote site — the site where the public can view your Web pages. You provided Dreamweaver with the information it needs to transfer the files from your Local site to your

Publishing a Dreamweaver Site

Remote site. Uploading your files to the Remote site is sometimes called "putting your files," based on the FTP command put, used to upload files. Dreamweaver handles the details of the connection to the remote server and transferring the files.

You can transfer your entire site or any single file to the Remote site. Because this example shows publishing your first Web site, the entire site is transferred. The Web site in this example actually consists of only one file and an empty Images directory. If more files exist in the Local site, all the files are transferred using the steps shown in this section.

ver 8 Beta 2 - [...s-local\Dr Click Window. View Insert Modify Text Commands Site Wind ≥^A_D B Z S cm ¶ E ✓ Insert Cirl+F2 dl dt dd atte wee 🖭 Text 7 Properties Cirl+F3 Click Files. CSS Styles Shift+F11 FirstPage.html 🗘 Code 📇 Spitt 📑 Design Title: First Page .ayers F2 Shift+F4 C E. G. Behaviors 10 0 0 0 0 × 2 0 0 0 0 Databases Orl+ShR+F10 **Sindings** Orl+F10 This is my first Dreamweaver page. Server Behaviors Cirl+E9 Ctrl+E7 Components 2 Files F8 Assets F11 Snippets shift-(E9 Tag Inspector E9 Results Reference shift-(FL History Shift+F10 Frames Shift+F2 Code Inspector F10 Timelines Altared Workspace Lavout: Hide Panels E4 Cascade Tile Horizontally The Vertically 🖌 i FirstPage.htm (a) (2) Q₆ 100% ∨ 705 × 40 The Files panel opens in the right-hand pane. wer 8 Beta 2 - [...ts\MyWebSites\site: FirstPage.html (XHTML) ▼ Files Click here and select a site. Text 🔻 № B / S em ¶ [***] PHE h1 h2 h3 ul ol li dl Files Assets Sr - @ × FirstPage.html Dreamweaverb: V Local view (4)4 Click the Upload button (\bigcirc) . 🕢 Code 📇 Split 📑 Design Title: First Page 57 P. M. G. C E. G 2 C 5 f 🔫 🗄 🔄 Site - DreamweaverBook (C:(D: Images FirstPage.html This is my first Dreamweaver page.

6

The Uploading window opens.

- Note: When the Uploading window disappears, the site has finished uploading.
- Open your browser.
- 6 Type the URL to your Web site.

Your Web site appears in your browser.



Address 🗃 http://janet.valade.com/DreamweaverBook/FirstPage.html <

🗿 First Page - Microsoft Internet Explorer File Edit View Favorites Tools Help

G Back • 🕤 -

Done

This is my first Dreamweaver page.



Internet



Do I need to save the Web pages before I publish them?

Dreamweaver transfers the saved versions of the files. However, if you currently have a file open with changes that have not been saved yet, Dreamweaver asks you whether you want to save the file before putting the file on the Remote site. If you click No, the Web page uploads without the current, unsaved changes.

Do I need to create the folder structure on my remote server before uploading my local site?

No. Dreamweaver duplicates the Local site folder structure on the Remote site. When Dreamweaver uploads a file from a local folder that already exists on the remote site, it puts the Web page into the existing folder. When Dreamweaver uploads a file from a local folder that does not exist on the Remote site. it creates the folder and then puts the Web page into the new folder.

How can I check that all the Web pages were correctly put on the remote site?

Dreamweaver displays the Local site and the Remote site side-by-side so you can see the structure and files on both. You can open this display from the Files panel. Click deside Local view, click Remote view, and then click the Expand button. Dreamweaver displays the folder/file names, file size, date last modified, and other information about the folders and files.

Copy a Dreamweaver Site

Dreamweaver site consists of the settings Dreamweaver needs to organize and manage the site Web pages. The settings include the site name, the path to the root folder where the Web site files are stored, the information needed to connect to the remote site, and other information. When you want to set up a new Dreamweaver site that is very similar to an existing Dreamweaver site, you can often save time by copying the existing site and changing only the information that is different, such as the site name and the path to the root folder.

The duplicate site has all the same settings as the original site. It is given the name *Sitename Copy*, such as DreamweaverBook Copy. You can then change the information for the duplicate site, such as the site name, as described in the section "Change Dreamweaver Site Information" earlier in this chapter.

Copy a Dreamweaver Site

Display the Manage Sites dialog box.

Note: See the section "Create a Dreamweaver Site" to display the Manage Sites dialog box.

- 2 Click the site name.
- 3 Click Duplicate.

- The duplicate site is added to the list of sites.
- You can click Edit to change the properties of the duplicate site.

4 Click Done.

_	Manage Sites	×	
2	DreamweaverBook Examples NetIdentity	New Edit Duplicate Remove Export Import	_3
	Done Manage Sites	Help	
•	DreamweaverBook DreamweaverBook copy Examples NetIdentity	New Edit Duplicate Remove Export Import	
4	Done	Help	

chapter

Set Up a Check-out System

arge Web sites consist of many files with more than one developer working on the files. In such a situation, a system to prevent developers from simultaneously working on the same files and overwriting each other's work is necessary. Dreamweaver provides a check-in/check-out system that prevents two developers from working on the same file at the same time.

The check-out system requires a developer to check out a file before changing it. While the developer has the file checked out, no one else can change the file. When the developer is through changing the file, he or she checks the file back in. The Dreamweaver check-in/check-out system is implemented on a per site basis. The check-out system must be turned on for each individual Dreamweaver site. You can enable the check-out system when you set up the Dreamweaver site. A check box labeled "Enable file check in and check out" appears in the dialog box when you are setting up the remote site.

If you did not enable the check-out system when you set up your Dreamweaver site, you can change the site settings to enable file check out, as described in the section "Change Dreamweaver Site Information" earlier in this chapter. You can then check in your site files.

Enable the system

- Open the Dreamweaver Remote site dialog box.
- 2 Click Enable file check in and check out (changes to).

Set Up a Check-Out System

One check box and two fields appear.

- **3** Leave Check out files when opening checked.
- 4 Enter your name and e-mail address.
- 5 Click OK.

Check in your local site

1 Click here and select the site.

- **Note:** If Files panel is not open, click Window and select Files.
- 2 Click the site.
- 3 Click the Check In button (
).
- **Note:** If the check-out system is not enabled, is grayed out.
- 4 Click OK.

All files in the site are checked in.

A locked icon (
) displays beside the filenames.



Check Files In and Out

arge Web sites, consisting of many files with more than one developer working on the files, require a check-out system to prevent developers from working on files simultaneously and overwriting each other's changes. Dreamweaver provides a check-out system that requires a developer to check out a file before changing it and prevents anyone else from changing the file while it is checked out.

When several developers work on a Web site, the Remote site is the most up-to-date version of the site. A developer's Local site might not contain the latest version of a file that another developer worked on. Therefore, files are checked into and out of the Remote site.

The file list in the Files panel shows the file status — a red check mark beside a file that is checked out, along with the name of the person who checked it out, and a lock beside files that are checked in. Files that you checked out show a green check mark.

A file can be checked in or out with or without its dependent files, such as images and style sheets. Unless you are going to change them, you do not need to check out the dependent files.

Check Files In and Out



The Files panel opens.

3 Click here and select the site.

4 Double-click a filename.

The Dependent Files dialog box opens.

5 Click Yes or No.



The Web page opens. 2⁴₂ B *I* S cov ¶ ([∞]) 202 hl h2 h3 ul A green check mark appears by the filename. 🕡 Code 🔁 Solt. 🗐 Design Tides First Para CISAN 1 0 0 0 0 × 5 0 0 0 6 Make the changes to the Web page. This is my first Dreamweaver page 6) New sentence 1. 7 Click 💁. The file is uploaded to the Remote site. The file status changes back to checked in. TNI) [Read Only]] 🗍 2Å B Z S cor ¶ (™) 202 hi h2 h3 ul ol Gode 2 Solt 3 Colign Tides * th Party 5 P. M. Q. CF COAD 1 0 0 0 0 0 × 0 0 0 0 This is my first Dreamweaver page New sentence 1.



How does Dreamweaver know whether a file is checked in or checked out?

Dreamweaver checks whether a lock file exists. The lock file is named *filename.ext.LCK* (for example, FirstPage.html.LCK). When the file is checked out, Dreamweaver creates this file in the local and remote sites. The lock file is not removed until the file is checked back in. Thus, if Dreamweaver finds the lock file, the file status is checked out; if no lock file exists, the file status is checked in.

How does Dreamweaver prevent me from changing a file without checking it out?

When a file is checked in, the copy of the file in the local site becomes Read Only. You can open the file and make changes, but you cannot save the file. Of course, you can manually change the file status so that you can write to it, using Windows commands, but end runs around the check-in system usually result in confusion, content loss, and possible disaster.

What do I do when I really need to work on a file that someone else has checked out?

When you set up the check-out system for your Dreamweaver site, Dreamweaver requests your name and e-mail address. In the Files panel, the name of the person who has checked out a file is listed beside the filename. The name is a link that, when clicked, allows you to e-mail the person who has the file. You can send the person a message letting him or her know you need to work on the file.