

Subject Index

- 3GPP, 38
 - LTE, 38
 - DL parameters, 42
 - requirements, 42
 - SAE, 38
- 802.11, 95
- 802.16, 172

- AF, 391
- AGC, 459
- algorithm
 - tree search, 523
 - Viterbi, 523
- ALT, 334
- APA, 35
- APC, 420, 433
- APP, 309
- AWGN, 275

- baseband, 24
- BER, 503
- Bessel function, 24
- BLAST
 - Diagonal, 18
 - Vertical, 18
- block codes, 18

- capacity gain, 30
- CC, 91
- CDD, 35, 382
- CDMA, 390
- channel
 - frequency selective, 17
 - multi-path, 22
 - time-variant, 17
- channel estimation, 247
 - blind, 12
 - blind estimation, 248
 - decision directed, 12
 - joint optimization, 248, 255
 - pilot assisted, 12
 - pilot-aided estimation, 248
- channel interleaver, 77, 90, 91, 96, 104
- Cholesky factorization, 279, 284
- CIR, 14, 22
- CM, 95, 110
 - BICM, 95, 110
 - BICM-ID, 95, 110
 - CM principle, 96
 - code memory, 98, 115
 - complexity, 98
 - generator polynomials, 115
 - grey mapping, 96
 - set partitioning, 96
 - TCM, 95, 110
 - TTCM, 95, 110
- code rate, 105, 107
- coding gain, 86, 88, 93, 105
- coherence time, 23
- computational complexity, 523
- constellation points, 503
- convergence rate, 523
- correlation function
 - time-domain, 24
 - Jakes, 24
- cost function
 - Euclidean distance-based, 503
- COST207 HT, 119
- CPS, 36, 419
- CRC, 396
- CSC, 518
- CSCF, 298
- CSD, 20, 515
- CSI, 36, 227
- CTF, 14
- CUS, 35, 419
- cyclic prefix, 24

- D-BLAST, 18
- DAF, 35, 384
- data stream, 495
- DCMC, 462
- DDCE, 13
- DDF, 35, 384
- decoder
 - turbo
 - parallel-concatenated, 551
 - serially-concatenated, 550
- delay spread
 - maximum, 24
 - RMS, 211, 215
 - time-variant, 211
- DF, 391
- DFDD, 385
- DFT, 211

- DHDC, 319
- diversity, 63, 71, 146, 192
 - frequency diversity, 175, 183, 192
 - spatial diversity, 119, 127, 194
 - time diversity, 132
- diversity gain, 30, 557
- diversity order, 73, 79, 90, 108
- Doppler
 - frequency
 - maximum, 23
 - normalized, 24
- Doppler frequency, 133, 257
 - maximum Doppler frequency, 133
 - normalized Doppler frequency, 73, 98, 114, 119
- DSDC, 324
- DSS, 172, 175
 - cross-relation matrix, 186
 - despreader, 175, 178
 - despreading, 184, 185
 - DSS codes, 178, 186
 - DSS groups, 178, 185, 187
 - hybrid DSS/FH, 172
 - hybrid DSS/SSCH, 173, 175, 184, 191, 192
 - spreader, 175, 177
- error propagation, 236
- Euclidean distance, 65
- factorization
 - Cholesky, 517
- FD-CTF, 14, 307
- FDMA, 390
- FEC, 499
- FH, 171, 172
 - complexity, 196
 - FH pattern, 172
 - frequency diversity, 175, 183, 192
 - frequency synthesizer, 172, 174
 - frequency-selective channels, 192
 - hybrid DSS/FH, 172
 - offline pattern pre-computation, 184
 - pattern reuse interval, 184
 - SFH, 173
 - Random SFH, 184
 - subbands, 174
 - Uniform SFH, 184
- SSCH, 172–175
 - active subcarrier selector, 178
 - complexity, 196
 - demapper, 176, 178
 - demapping, 184
 - full permutation, 181
 - hybrid DSS/SSCH, 173, 175, 184, 191, 192
 - imperfect CSI, 196
 - mapper, 175, 176
 - notations, 188
 - ON–OFF signalling, 176
 - pattern design, 178
 - Random SSCH, 180
 - receiver structure, 178
 - remaining user set, 180
 - subcarrier groups, 180
 - total system throughput, 188, 193
 - transmitter structure, 176
 - uniform pattern set, 180
 - Uniform SSCH, 173, 180
- Fourier transform, 24
- FS, 14, 569
- FS-CIR, 25
- fully loaded, 500, 503, 506
- fully loaded systems, 139
- fully-loaded systems, 117, 158
- GA-JCEMUD
 - channel gene, 255
 - complexity, 258, 259
 - cross-over, 256
 - blend cross-over, 256
 - Doppler frequency, 257, 261–263, 265
 - FD-CHTF chromosome, 255
 - FD-CHTF estimation MSE, 261
 - final-iteration trigger, 252
 - first-stage MUD, 250, 253
 - fitness, 256
 - GACE-OHRSA-MUD, 264
 - error propagation, 265
 - serial concatenation, 264
 - individual, 255
 - individual-based output, 258, 259, 265
 - joint optimization, 255, 257, 263
 - LLR, 258
 - MIMO robustness, 265
 - multi-variate complex Gaussian distribution, 258
 - mutation, 256, 257
 - maximum mutation step size, 257, 260, 261, 587
 - step mutation, 257
 - normalization factor, 259
 - number of iterations, 263
 - objective function, 256, 259
 - objective score, 256, 259
 - offspring, 256
 - pilot controller, 250
 - pilot overhead, 253, 263
 - pilot symbol, 250, 252
 - population-based output, 258, 265, 587
 - schematic, 249
 - significant-tap catching, 250
 - soft output, 248, 258, 265, 587
 - symbol chromosome, 255
 - symbol gene, 255
 - time-domain filtering, 250
- GA-MMSE, 19
 - gain, 71, 73, 146
 - E_b/N_0 gain, 160
 - coding gain, 75, 87, 103
 - spreading-induced E_b/N_0 gain, 127
- Gaussian
 - complex, 22
- Grammian matrix, 279, 284
- GSD, 284
- Hermitian transpose, 112
- highly overloaded systems, 192
- HIHO, 35
- HT, 380
- IEEE standards
 - 802.11, 1, 38–41, 95
 - 802.11-1997, 38
 - 802.11-1999, 38
 - 802.11-2007, 38
 - 802.11a-1999, 38
 - 802.11b-1999, 38
 - 802.11d-2001, 38
 - 802.11e-2005, 38
 - 802.11g-2003, 38
 - 802.11h-2003, 38
 - 802.11i-2004, 38
 - 802.11j-2004, 38

- 802.11k-2008, 38
- 802.11n, 38
- 802.11r-2008, 38
- 802.11y, 38
- 802.16, 1, 41, 43, 172
 - 802.16-2001, 41
 - 802.16-2004, 43, 48
 - 802.16a-2003, 42
 - 802.16c-2002, 42
 - 802.16d-2004, 43
 - 802.16e-2005, 43, 44, 48
 - 802.16f-2005, 45
 - 802.16g-2007, 45
 - 802.16h, 45
 - 802.16j, 46
 - 802.16k-2007, 45
 - 802.16m, 52
 - PHY profiles, 44
 - WirelessMAN, 44
- IIR, 347
- IMT-Advanced, 52
- Ir-DHCD, 462
- IrCCs, 35
- ISR, 279

- Kronecker delta function, 23

- LDPC, 76, 90, 103, 260
 - code rate, 77, 79–81, 86, 88
 - codeword, 76
 - column weight, 76, 77, 86
 - complexity, 86, 87, 91
 - information bits, 76
 - irregular, 76
 - parity check matrix, 76
 - regular, 76
 - row weight, 76
- leakage, 25, 215
- LLR, 309, 531
- log-likelihood, 503
- Log-MAP, 70, 86, 91, 98, 532
 - complexity, 86, 91, 98
 - OHRSA, 533
- LOS, 357
- LS, 14

- MAMC, 21, 549, 586
- MAP, 68, 70, 91
 - complexity, 70
- matrix
 - direct product, 526
 - Hermitian, 517
 - positively definite, 517
 - upper-triangular, 517
- maximum likelihood detector, 65
- MCF, 534
- MED, 365
- MGF, 424
- MI, 319
- MIMO, 2, 517
 - advantages, 5
 - channel estimation, 247
 - blind estimation, 248
 - pilot-aided estimation, 248
 - channel matrix, 110, 248
 - MIMO OFDM
 - main contributions, 6–8
 - MIMO-OFDM, 5
- ML, 276–278, 501
- MMSE, 14, 497, 499
- moderately overloaded systems, 190, 191
- modulation scheme
 - M*-QAM, 516
 - BPSK, 527, 534
 - constant-envelope, 518
 - multi-level, 516
- MRC, 422
- MSDD, 385
- MSDSD, 384
- MSI, 364
- MU-MIMO, 35, 358
- MUD, 18, 109
 - GA MUD, 142
 - binary encoding, 143
 - BQM, 149, 187
 - CNUM, 152
 - complexity, 146
 - cross-over, 599
 - dominated individual, 143, 598
 - elitism, 143, 600
 - fitness, 143, 598
 - fitness-proportionate selection, 143, 599
 - gene, 148, 597
 - generation, 142, 597
 - hard-decision output, 248, 258, 259, 265
 - incest prevention, 143, 599
 - individual, 142, 597
 - iterative detection, 187
 - mating pool, 143, 598
 - mutation, 143, 600
 - mutation probability, 148, 587
 - non-dominated individual, 143, 598
 - objective function, 142, 598
 - objective score, 143, 598
 - offspring, 143, 599
 - parent, 143, 599
 - Pareto-Optimality, 143, 598
 - population, 142, 597
 - simplified BQM, 152
 - soft output, 248, 258, 265, 587
 - transition probability, 148
 - transition probability normalization, 601
 - uniform cross-over, 143, 600
 - uniform mutation, 148
 - windowing-mapping, 143
 - IGA MUD, 155, 187
 - E_b/N_0 gain, 160
 - 2D optimization, 156
 - codeword domain, 156
 - complexity, 165
 - frequency domain, 156
 - imperfect CSI, 164
 - user domain, 156
 - ML MUD, 141
 - complexity, 141, 146
 - MMSE MUD, 112, 186
 - OHRSA MUD, 250, 253, 589
 - constrained MMSE-based estimate, 254
 - unconstrained MMSE-based estimate, 254
 - weighted Euclidean distance, 254
- MUI, 118, 171, 175, 179, 191, 369
- multiplexing gain, 503
- MV, 497

- NLOS, 22
- NMSE, 204
- Nyquist filter, 28
 - raised cosine, 24

- OF, 279
- OFDM, 1, 95, 96, 109, 275–276
 - cyclic extension, 96
 - interleaved OFDM, 175
 - ISI, 96
 - main contributions, 4
 - milestones, 3
 - MIMO OFDM
 - main contributions, 6–8
 - MIMO-OFDM, 5
 - OFDM-symbol-invariant channel, 113, 144, 188, 260
 - subcarrier, 96
- OFDMA, 172
- OHRSA, 19, 515
 - Log-MAP, 537
 - ML, 527, 534
- OSTBC, 360
- overloaded, 500, 507, 516
- overloaded systems, 140, 161, 173, 183, 191, 192, 248, 259, 262

- PAST, 211
- PDF, 205
- PDP, 14, 22, 569
- PED, 280
- performance
 - error-free, 22, 561, 586
- PIC, 18
- PLR, 429
- point-to-point, 18
- probability
 - outage, 554
- PSD, 23
 - band-limited, 24
 - U-shaped, 24
- PSK, 505

- QAM, 505
- QPSK, 499

- RA, 380
- Random SFH, 184
- Random SSCH, 180
- rank-deficient, 559
- Rayleigh, 14, 17, 22, 569
- receiver
 - iterative, 549
 - turbo, 549
- recursive tracking
 - LMS, 233
 - RLS, 236
- RMS, 215
- RSA, 20, 515, 585
- RSC, 313, 499

- SCF, 298
- SD, 20, 278, 515
 - K -best SD, 283
 - breadth-first SD, 283
 - depth-first SD, 279–282
 - GSD, 284–285, 297
 - ISR, 287, 289–290
 - LSD, 310
- SDM, 17
 - detection, 19
 - CSD, 20, 515
 - GA-MMSE, 19, 501, 508
 - linear, 504
 - LS, 18
 - ML, 19, 501
 - MMSE, 500
 - non-linear, 501
 - OHRSA, 515
 - PIC, 18
 - SIC, 18, 19, 501, 504
 - SOPHIE, 515
- SDMA, 6, 18, 109, 110, 275–276
 - advantages, 7
 - conventional SDMA-OFDM, 171, 173, 197
 - main contributions, 10, 11
 - spatial signatures, 194
- SDMD, 19
- search
 - branch, 534
 - legitimate, 523
 - low likelihood, 536
 - exhaustive, 523
 - global, 508
 - recursive, 527
 - tree, 536
- SIC, 18
- SIC-MMSE, 329
- SINR, 497, 504
- SIR, 497
- smart antennas, 17
- soft-bit, 503
- SOPHIE, 515
- SP, 35, 359
- SS, 14, 569
- SSD, 291, 292
- SSD-TT, 293
- SSD-UB, 292
- STBC, 18, 35, 63, 66, 70, 75, 90, 95
 - G_2 code, 64, 68, 71, 79, 92, 97, 100, 103
 - G_3 code, 66, 71, 79, 106
 - G_4 code, 66, 71, 79, 106
 - H_3 code, 67, 79, 107
 - H_4 code, 67, 79, 107
 - code rate, 66, 67
 - coding gain, 75, 87, 103
 - complexity, 86
 - decoding algorithm, 67
 - diversity gain, 71, 73
 - encoding algorithm, 66
 - MAP, 68
 - aposteriori probability, 68
 - Log-MAP, 70
 - Max-Log-MAP, 70
 - soft output, 69
 - symbol-by-symbol MAP, 68
 - symbol-to-bit probability, 69
 - maximum likelihood decoding, 67, 69
 - decision metric, 68
 - quasi-static, 70, 98
 - time slot, 64
 - transmission matrix, 66, 67
- STC
 - trellis codes, 18
- STTC, 18
- SU-MIMO, 35, 359
- subcarrier BER, 114
- subcarrier-related, 24
- synchronization, 178
- system instability, 560
- system model
 - discrete frequency-domain, 28
 - real-valued, 527

- TC codes, 91
 - complexity, 91
 - turbo decoding, 91
 - turbo interleaver, 96
- TD, 382
- TDMA, 390
- TH, 380
- throughput, 64, 96
 - effective throughput, 71, 78, 90, 96
 - total system throughput, 188, 193
- TT, 300
- turbo codes, 76, 91, 96
- turbo coding, 499

- UL, 275, 343
- underloaded systems, 139, 158
- Uniform SFH, 184
- Uniform SSCH, 180
- URC, 35, 318, 343
- user load, 116
 - fully loaded systems, 139
 - fully-loaded systems, 117, 158
 - highly overloaded systems, 192
 - moderately overloaded systems, 190, 191
 - overloaded systems, 140, 161, 173, 183, 191, 192, 248, 259, 262
 - underloaded systems, 139, 158

- V-BLAST, 18, 291, 495
- VAA, 379

- WHT, 29, 110
 - block size, 132
 - orthogonal codes, 112
 - spreading-induced E_b/N_0 gain, 127
 - subcarrier spreading, 110, 112
 - WHT despreader, 111
 - WHT spreader, 111
 - WHTS, 111, 112, 178
- Wi-Fi, 37, 38
 - Wi-Fi Alliance, 37
- WiBro, 47
- WiMAX, 40
 - product development, 58
 - WiMAX Forum, 46
 - WiMAX-I, 48
 - channel coding, 50
 - frame structure, 48
 - FUSC, 48, 50
 - HARQ, 52
 - MIMO support, 50
 - OFDMA parameters, 48
 - PHY features, 53
 - PUSC, 48, 50
 - subcarrier mapping, 49
 - synchronization, 52
 - WiMAX-II, 52
 - system description, 54
 - system requirements, 52
- WSS, 22

