
1

INTRODUCTION

In the first widely available book on *Forest Mensuration* in North America, Henry S. Graves (1906) wrote: “Forest mensuration deals with the determination of the volume of logs, trees, and stands, and with the study of increment and yield.” *The Dictionary of Forestry* (Helms, 1998) states that “Forest mensuration is the determination of dimensions, form, weight, growth, volume, and age of trees, individually or collectively, and of the dimensions of their products.” This definition is essentially a paraphrase of the 1906 definition given by Henry S. Graves. Although some foresters feel this definition is still adequate, this text considers that mensuration should embrace new measurement problems that have arisen or have been recognized as the horizons of forestry have expanded.

If we accept the challenge of a broader scope, we must ask: “To what degree should mensuration be concerned with measurement problems of wildlife management, recreation, watershed management, and the other aspects of multiple-use forestry?” One might argue that it is unrealistic to imagine that forest mensuration can take as its domain such a diverse group of subjects. The objection becomes irrelevant if we recognize forest mensuration, not as a collection of specific techniques, but as a subject of study that provides principles applicable to a wide range of measurement problems. We view the measurement and quantification of all aspects of forest vegetation as within the domain of forest mensuration. Moreover, many ideas, approaches, and techniques have been developed within the context of traditional forest mensuration that have broad applicability for forest ecology, wildlife habitat, recreation, and watershed management. This book, in addition to a treatment of the traditional product-oriented measurement problems of forestry, will also provide a unified foundation of principles for solving measurement problems in other aspects of forestry.

During the latter half of the twentieth century, the application of statistical theory and the use of computers, electronics, and lasers wrought a revolution in the solution of forest

measurement problems. Consequently, mensurationists must have a degree of competence in their use as well as in basic mathematics and statistics. Knowledge of calculus is also desirable. In addition, familiarity with systems analysis and operational research, approaches to problem solving that depend on model building and techniques that include simulation and mathematical programming, will also be valuable, especially in advanced and more sophisticated treatments of forest mensurational problems. We do not presume that all readers of this text will have such a deep and broad background, and have tried to present forest mensuration in a way that is accessible to new students but provides a comprehensive overview of the possibilities of the field.

1.1. ROLE OF FOREST MENSURATION IN FOREST MANAGEMENT

Forest mensuration is one of the cornerstones in the foundation of forestry. Forestry in the broadest sense is a management activity involving forest land, the plants and animals on the land, and humans as they use the land. Much of the forest land in North America and in other parts of the world is under active forest management. In many jurisdictions, foresters are required to complete detailed long-term forest management plans, especially on public lands. These plans require foresters to make detailed predictions about the growth and yield of forest resources, and how harvesting and other forest management activities influence the flow of timber and other resources. Based on the outputs from these models, forest managers make decisions about where, when, how, and how much forest land should be treated. Elsewhere, management planning may reflect shorter time horizons, but the decisions are no less critical. Good forest management decisions require good tools to analyze the impacts of management activities on the quantities and flows of the various forest resources and on the state of the forest itself. These tools require good models and, ultimately, these models require good data. The acquisition of this data is the subject of this book.

Foresters are faced with many decisions in the management of a forest. The following questions are examples of the problems that must be solved for a particular forest:

1. What silvicultural treatment will result in best regeneration and growth?
2. What species is most suitable for reforestation?
3. Is there sufficient timber to supply a forest industry and for an economical harvesting operation?
4. What is the value of the timber and land?
5. What is the recreational potential?
6. What is the wildlife potential?
7. What is the status of biodiversity on the area?
8. What is the status of the forest as a carbon sink?

A forester needs information to answer these and countless other questions and to make intelligent decisions or recommendations to a client. This information often is needed in quantifiable terms. In most situations, the axiom holds, "You can't efficiently make, manage, or study anything you don't locate and measure." At the same time, resources for measurement are usually limited, so information must be acquired efficiently. In this sense,

forest mensuration is the application of measurement principles to obtain quantifiable information for forest management decision-making.

To summarize, *forest mensuration* is concerned with obtaining information about forest resources and conditions. The ultimate objective of forest mensuration is to provide quantitative information about the forest and its resources that will allow making reasonable decisions on its destiny, use, and management.

1.2. FOREST MENSURATION AS A TOOL FOR MONITORING FORESTS

To many, a forest, if not affected by cutting, fire, or some other calamity, is a stable, unchanging entity. Actually, a forest is a dynamic system that is continuously changing. Although this may not be evident over a short term, such as a few years, change is always present: some trees increase their dimensions, others die, and new trees germinate and enter the forest. Consequently, the information obtained about the status of a forest area at a given time is only valid for a length of time that depends on the vegetation itself, and on environmental and external pressures affecting the forest. This means that the mensurational information regarding the forest must be updated periodically by monitoring procedures so that the appropriate management and policy decisions may be taken.

Throughout the twentieth century, the demand on forest resources increased worldwide (Westoby, 1987). In the opening decades of the twenty-first century, this increase is expected to continue. During the last 40 years, not only have the demands for timber increased, foresters also have been required to manage for other resources including wildlife habitat, water quality, recreational opportunities, and biodiversity. An increase in the public awareness of the influence of human activities on the environment has resulted in the development of a number of forest certification procedures to ensure that forest management activities are sustainable both economically and environmentally. These procedures require forest managers to document and monitor the impacts of forest management activities on a wide range of forest resources, not just timber.

Monitoring must consider changes in composition, structure, size and health of forests (Max et al., 1996). To be effective, monitoring must be comprehensive. In these situations, foresters must increase the scope of their inventories, and the models they use, to include information on multiple aspects of forest structure, not just timber-producing trees. To be cost effective, forest managers will be required to design and implement new sampling strategies and measurement procedures to meet the demand for increased information.

In the early 1900s, as professional forestry was beginning in North America, the need to use the quantitative tools forest mensuration and forest inventory offered to monitor forest resources was quickly recognized (Bates and Zon, 1922). Zon (1910), in one of the first attempts to assess global forest resources, recognized the need for systematic monitoring of forest resources on both a national and global basis. The Scandinavian countries (Norway in 1919, Finland in 1920, and Sweden in 1923) were the first countries to implement systematic national forest inventories (NFIs) based on modern statistical principles (Tokola, 2006; Tomppo, 2006). The United Kingdom began NFIs in 1924 and the United States in 1930. The Food and Agricultural Organization of the United Nations began compiling global assessments of forest resources in 1947. Many other European and Asian countries began NFIs in the 1960s and 1970s. In the late 1980s and early 1990s, many countries, including the United States and Sweden, redesigned their NFIs, adopting a

systematic-grid-based sample design and consistent plot designs and remeasurement intervals. A number of countries around the world have redesigned or adopted similar protocols for their NFIs. Although most NFIs began with a focus on timber and related resources, nearly all are actively broadening to address the full range of economic, conservation, and environmental challenges faced by regional and national policymakers. Most countries have also integrated remote sensing, aerial photography, and/or LiDAR data into the analyses of ground-based data.

While the various NFIs differ by the specific measurements made, plot sizes and layouts, grid intensities, and remeasurement intervals, the newer designs make it easier to compare estimates across countries (Liknes et al., 2013). The information collected has many important uses including

1. helping policymakers at national and regional levels to formulate good forest policy, and to assess the sustainability of current and past policy;
2. enabling land managers to devise better management plans and to assess effects of current and past management practices on the land;
3. serving as a starting point for scientific investigations in a variety of areas that involve changes in forest ecosystems over time;
4. formulating business plans that will be both economically and ecologically sustainable over time;
5. keeping the public informed about the health and sustainability of a nation's forests; and
6. providing consistent and reliable reporting statistics to demonstrate compliance with various treaty obligations including conservation and biodiversity commitments and carbon offset accounting.

Most countries provide online access to their NFI data and extensive online report generating capabilities.

1.3. RELEVANCE OF FOREST MENSURATION FOR ECOLOGY AND NONTIMBER RESOURCES

Ecologists, conservation biologists, and wildlife managers, like forest managers, require quantitative information to make informed decisions. Sometimes, these decisions are about choices of management actions, and sometimes about choices between competing scientific hypotheses; but either type of choice depends on high-quality data that are collected and analyzed in a cost-effective way. While the emphasis of this text is the measurement, sampling, and estimation of the tree component of the forest vegetation, the basic principles of mensuration can be applied to a range of forest structures and attributes, and we have included some coverage of measurements for these characteristics. Estimation of species diversity, abundance, biomass, and carbon content utilize similar techniques for measurement and sampling, whether the focus is on trees, shrubs, herbs, or grasses. Of course, the types of measurements made, the tools used, the size, shape, and type of sample plots, and the sample intensity will vary depending upon the size of individuals, the spatial heterogeneity, and the estimates required (Bonham, 2013).

Ecological studies require measurements that are effective, accurate, and precise (Ford, 2000). Many of the stand structure parameters useful to foresters for making management decisions (e.g., density, basal area, volume, biomass, and crown cover) are useful parameters for estimating nontimber resources and ecological indices. Wildlife managers often rely on measures of stand structure to assess habitat quality and suitability. The need for accurate measurements and robust sample designs are just as important for these applications as they are for timber management.

An unfortunate consequence of the increasing channelization and specialization of knowledge in the twentieth and twenty-first century has been the divergence of scholarship and teaching between those working in areas of forestry most closely related to timber management, and those working in areas that have more conventionally been the domain of programs in ecology and conservation biology. Our view is that the two groups have much to learn from each other. Recent decades have seen dramatic advances in sampling techniques and forest measurements designed with timber applications in mind, but many of these advances are not widely known even though they have direct application to other challenges in forestry, forest conservation, and ecology in general. Conversely, some foresters whose training is narrowly focused on timber production have found the emerging science and practice in areas related to biodiversity or carbon accounting a bit mysterious, even though the basic measurement principles—and even some of the techniques—are quite similar to those they already know. An integrated treatment of these areas of forest mensuration will help both scientists and professionals approach forests with greater technical versatility and a broader outlook.

1.4. DESIGN AND PLANNING OF INVENTORIES

A *forest inventory* is the procedure for obtaining information on the quantity, quality, and condition of the forest resource, associated vegetation and components, and many of the characteristics of the land area on which the forest is located. The goals of a forest inventory depend on the management and policy questions it is designed to support. Most forest inventories have been and will continue to be focused on timber estimation. The need for information on forest health, water, soils, recreation, wildlife and scenic values, and other nonwood values has stimulated the development of integrated or multiresource inventories (Schreuder et al., 1993; Lightner et al., 2001). Interest in forests as a carbon sink has generated considerable interest in estimating forest biomass and carbon content (Satoo and Madgwick, 1982; Brown, 2002; Smith et al., 2006; Pearson et al., 2007). Development and execution of multiresource inventories often requires cooperation among many specialists in pertinent fields.

1.4.1. Timber Estimation

A complete forest inventory for timber evaluation provides the following information: estimates of the area, description of topography, ownership patterns, accessibility, transportation facilities, estimates of timber quantity and quality, and estimates of growth and drain. The emphasis placed on specific elements will differ depending upon the purpose of the inventory (Husch, 1971). For example, if the purpose of an inventory is for the preparation of a harvesting plan, major emphasis would be put on a description of topography, determination of accessibility and transportation facilities, and estimation of timber quantity.

Other aspects would be given little emphasis or eliminated. If the purpose of an inventory is for the preparation of a management plan, major emphasis would be put on timber quantity, growth, and harvest levels with lesser detail on other aspects.

Information is obtained in a forest inventory for timber evaluation by measuring and assessing the trees and various characteristics of the land. The information may be obtained from measurements made on the ground or from remotely sensed data (aerial photographs, satellite imagery, or LiDAR*). When measurements are made on all trees in a forest, the inventory is a complete or 100% inventory. When measurements are made for a sample of the forest, it is a sampling inventory. The terms *cruise* in North America and *enumeration* in other English-speaking areas are frequently used instead of inventory.

In executing a forest inventory for timber evaluation, even one based on a fairly small sample, it is impossible to measure directly quantities such as volume or weight of standing trees. Consequently, a relationship is established between directly measurable tree or stand characteristics (e.g., dbh, height) and the desired quantity. This may be done as follows:

1. Make detailed field measurements of trees or stands and compute the desired quantities from these measurements. For example, one might make detailed diameter measurements at determined heights along the stem of standing trees and determine volumes by formulas or graphical methods (Section 6.1).
2. Estimate the desired quantities in trees or stands by utilizing relationships previously derived from other trees or stands. For example, one might measure tree or stand characteristics such as dbh, height, and form, and determine the corresponding volume or weight from an equation or a table (Section 6.2).

Timber inventories can estimate gross and net volumes. An estimate of *gross volume* shows the volume of wood, usually without bark, based on the exterior measurements of the trees: dbh, height and, form, without any deductions for defects. An estimate of *net volume* reduces the gross volume due to defects such as rot, diseased portions, and stem irregularities. The reduction for defect can be determined in two ways: (1) at the time of measurement of each tree, the external defects can be noted, internal defects estimated (or directly determined by boring) and recorded, and the loss in volume estimated per tree; and (2) by applying a cull factor expressed as a percent that will reduce the gross volume of the inventory to net volume. This cull percent can be determined directly by carrying out a study that requires the felling of a sample of trees and determining their gross and net volumes to determine cull percentages. Frequently cull percentages are based on previous experience in the kind of timber being inventoried. Inventories can be designed to estimate net volumes or quantities by product classes such as poles, pulpwood, sawtimber, and veneer logs. Of course, this requires specifying the criteria to be used at the time of measurement of sample trees during fieldwork.

Other factors in estimating net usable quantity of timber depend not on the defects in the trees themselves but on several external causes. Impacts of factors such as accessibility, legal restrictions (protected areas, silvicultural requirements, and harvesting restrictions), nonutilizable species, minimum quality characteristics and sizes of logs, and losses due to breakage in logging and transport are required to obtain an estimate of the usable net volume.

*Light Detection and Ranging, Section 13.1.4.

1.4.2. Nontimber Estimation

As Hassan et al. (1996) have pointed out, “the need to look into non-wood benefits of forestry is ... becoming an increasingly important component of forest management planning in view of the fact that the contribution of forestry goes beyond wood production.” The parameters measured in multiresource inventories vary, depending on the information required. These parameters may include timber estimates together with data on nontimber vegetation and/or other forest characteristics, such as biodiversity, forest health, scenic values, recreation resources, water quality, wildlife habitat, carbon storage, and ownership (USDA, 1992).

Multiresource inventories require considerations in the design and implementation that generally are not required when designing timber inventories. Tree species have large woody structures that persist throughout the year, making identification and quantification relatively easy in most seasons. Many nontree species, on the other hand, have ephemeral structures that may only be present on a site for a relatively short period during the growing season. Nontree vegetation assessments require fieldwork to coincide with periods in which ephemeral species are actively growing and identifiable on the site. Different species also vary in the timing of their growth, with some species present early in the growing season and others later. Estimates of total vegetation diversity may require multiple visits to the same sites (Rosenzweig, 1995; Li et al., 2008). While many of the measurement and sampling techniques used for tree species can be adapted to nontree species, different assessment methods are required depending on whether presence, counts, biomass, or cover estimates are required. Sample designs will also need to be modified since the spatial variability of nontree species is often much finer than for tree species.

Assessment of wildlife poses similar considerations. Wildlife may be directly assessed or the forest structure might be assessed for either signs of use or its suitability for use by particular species. Direct assessment of wildlife populations is beyond the scope of this text, and the reader is referred to textbooks specializing in wildlife population estimation (Buckland et al., 2001, 2004; Braun, 2005). Estimation of suitability often relies on models that predict habitat suitability for a given species based on forest vegetation attributes found to be correlated with wildlife use or abundance (Morrison et al., 1992). Often, variables used in habitat suitability models are the same as those estimated in timber inventories; however, some require additional measurements such as canopy cover, browse availability, presence of snags, cavities, or down woody debris, and nontree vegetation density.

Water quality, soils, and forest health have specialized variables of interest that may require additional measurements other than those commonly made in timber inventories, though models relating forest structure to these variables are often used (Anhold et al., 1996; Rheinhardt et al., 2012; Fernandes et al., 2014). Recreation value and scenic values are similarly estimated using forest structure attributes and models predicting recreation and scenic values based on user preference surveys (Ribe, 1989).

1.4.3. Inventory Planning

An important step in designing a forest inventory is the development of a comprehensive plan before initiating work. Such a plan ensures that all facets of the inventory, including the data to be collected, financial and logistical support, and compilation procedures, are thought through before the inventory begins. The student is referred to Husch (1971) for a discussion of inventory planning.

The following checklist includes all, or almost all, items that should be considered in planning a forest inventory. The items do not always have the same importance, and are not needed in all plans.

1. Purpose of the inventory
 - a. Timber and nontimber parameters to be estimated
 - b. How and by whom the information will be used
2. Background information
 - a. Past surveys, reports, maps, photographs, and so on
 - b. Individual or organization supporting the inventory
 - c. Funds available
3. Description of area
 - a. Location
 - b. Size
 - c. Terrain, accessibility, transport facilities
 - d. General character of forest
4. Information required in final report
 - a. Tables and graphs
 - b. Maps, mosaics, or other pictorial material
 - c. Narrative report
5. Inventory design
 - a. Estimation of area (from aerial or orthographic photographs, maps or field measurements)
 - b. Determination of timber quantity (e.g., volume tables, units of volume, etc.)
 - c. Methods for estimation of nontimber parameters (e.g., nontimber forest products, regeneration, understory vegetation, dead wood, soil, water, scenic and recreational values)
 - d. Size and shape of fixed-size sampling units
 - e. Probability sampling
 - (i) Simple random sampling
 - (ii) Systematic sampling
 - (iii) Stratified sampling
 - (iv) Multistage sampling
 - (v) Double sampling
 - (vi) Sampling with varying probability
 - f. Nonrandom or selective sampling
 - g. Setting precision for inventory
 - h. Sampling intensity to meet required precision
 - i. Times and costs for all phases of work
6. Procedures for interpretation of photo, satellite imagery, or other remote sensing material
 - a. Location and establishment of sampling units
 - b. Determination of current stand information, including instructions on measurement of appropriate tree and stand characteristics coordinated with fieldwork

- c. Determination of insect damage, forest cover types, forest fuel types, area, and so on, coordinated with fieldwork
 - d. Personnel
 - e. Instruments
 - f. Recording of information
 - g. Quality control
 - h. Data conversion and editing
7. Procedures for fieldwork
 - a. Crew organization
 - b. Logistical support and transportation
 - c. Location and establishment of sampling units
 - d. Determination of current stand information, including instructions on measurement of trees and sample units coordinated with photo interpretation
 - e. Determination of growth, regeneration, insect damage, mortality, forest cover types, forest fuel types, area, and so on, coordinated with photo interpretation
 - f. Instruments
 - g. Recording of observations
 - h. Quality control
 - i. Data conversion and editing
8. Compilation and calculation procedures for reduction of remote sensing and field measurements
 - a. Conversion of remote sensing material or field measurements to desired expressions of quantity
 - b. Calculation of sampling errors
 - c. Specific methods and computer programs to use
 - d. Description of all phases from handling of raw data to final results, including programs
9. Final report
 - a. Outline
 - b. Estimated time to prepare
 - c. Personnel responsible for preparation
 - d. Method of reproduction
 - e. Number of copies
 - f. Distribution
10. Maintenance
 - a. Storage and retrieval of data
 - b. Plans for updating inventory

The decision to conduct an inventory depends on the need for information. An inventory is an information-gathering process that provides one of the bases for rational decisions. These decisions may be required for many reasons such as the purchase or sale of timber,

for preparation of timber-harvesting plans, in forest and wildlife management, for obtaining a loan, and so on. If the purpose is clarified, one can foresee how the information will be used and know the relative emphasis to put on the different elements of the inventory.

As a first step in planning an inventory, one should obtain the requisite background information and prepare a description of the area. One should then decide on the information required from the inventory and prepare the outlines of tables that will appear in the final report. Table outlines should include titles, column headings, class limits, measurement units, and other categories needed to indicate the inventory results. These table outlines should be prepared before detailed planning begins because the inventory design will depend on the information required for the final report. Area information is usually shown by such categories as land use class, forest-type or condition class, and ownership. Timber quantities are usually given in stand-and-stock tables. A *stand table* gives number of trees by species, dbh, and height classes. A *stock table* gives volumes or weights according to similar classifications (see Chapter 9 for details on construction of stand and stock tables). Stand and stock tables may be on a per unit area basis (per acre or hectare) or for the total forest area and may be prepared for forest types or other classifications (e.g., compartments, watersheds). Since a forest is a living, changing complex, the inventory plan should consider the inclusion of estimates of growth and drain. For a discussion of tree and stand growth, see Chapter 14.

1.4.4. Forest Inventory Design

There must be wide latitude in designing an inventory to meet the variety of forest vegetation, topographic, economic, and transportation conditions that may be encountered. The required forest inventory information can be obtained by observations and measurements in the field and on aerial photographs, satellite images, and other remote sensing sources. The most useful and practical approach is typically to use remote sensing materials for forest classification or stratification, mapping, and area determination, and to employ ground work for detailed information about forest conditions, timber quantities and qualities, and additional nontimber characteristics. One can design a forest inventory utilizing only fieldwork, but it is usually less efficient unless the area under consideration is quite small. If aerial photographs or satellite imagery are available, they should be used. Under some circumstances, it is possible to design a forest inventory based entirely on photographic or remotely sensed interpretations and measurements; however, this method will provide only rough approximations of timber species and the quantity, quality, and sizes present, and information on the nontimber parameters; ground-based reference data are almost always needed to evaluate the accuracy of the remote sensing work, and to provide estimates of those quantities that cannot easily be observed from an aircraft or satellite (uses of remotely sensed data are discussed in Chapter 13).

The funds available and the cost of an inventory will strongly influence the design chosen. The main factors that will affect costs are the type of information required, the standard of precision chosen, the total size of the area to be surveyed, and the minimum size of the unit area for which estimates are required. General information is relatively inexpensive, but the costs increase, as more details are required. The standard of precision chosen greatly influences costs; costs increase since increases in precision usually require more intensive sampling. Costs per unit area will decrease as the size of the inventory area increases. If independent estimates are required for subdivisions of a large forest area, this will also raise costs. Descriptions of basic sampling designs applicable to forest inventory are given in Chapter 10.

1.4.5. Inventory Fieldwork

The size and organization of field crews will vary with sampling procedures, the observations or measurements required, forest conditions, and tradition. For timber inventory work in temperate zone forests, crews of one or two workers are widely used. If additional non-timber information is required, additional members may be needed. Small-sized crews have proved satisfactory in these areas because roads are usually abundant (access by vehicle is good), forest travel is relatively easy (little brush cutting is required), and well-trained technicians are generally available (they require little supervision). For inventory work in tropical forests, large crews are widely used because roads are generally sparse (access by vehicle is poor), forest travel is difficult (workers are required to cut vegetation), and few trained technicians are available (they require considerable supervision). Whatever the crew size or the assigned tasks, specific, clear instructions should be given to each crewmember.

A basic rule of forest inventory is to prepare complete written instructions before fieldwork starts. To minimize later changes, instructions should be tested before operations begin. Instructions should be clear and specific enough so that individual judgment by field crews on where and how to take measurements is eliminated. For example, field crews should not be permitted to subjectively choose the position of a sampling unit or to move it to a more accessible position or more "typical" stand. The aim should be to standardize all work to obtain uniform quality and the best possible reliability of the measurements, regardless of which individual does the work. The occurrence of mistakes or nonrandom errors must be eliminated or, at least, held to a minimum.

It is best to settle on a standard set of instruments. The use of several kinds of instruments to make the same type of measurements should be avoided. To minimize errors, the instruments should be periodically checked to see if they are in adjustment.

Decisions should be made on the precision required for each of the measurements. Thus, tree diameters may be stipulated to the nearest centimeter, inch, tenth of an inch, and so on, and heights to the nearest foot, meter, one-half log, and so on. If estimates of timber quantity are to be made by quality or product classes, then field instructions must include tree measurement specifications of minimum dbh and upper stem diameter, section lengths, and total usable length and criteria such as crook, scars, catfaces, evidence of rot, and so forth on individual sections and for the entire tree.

Inventory field operations must include a checking or quality control procedure. Whether plots, strips, or points are used, a certain percentage of the sampling units should be remeasured. The results of the remeasurements should be compared to the original measurement to see if the work meets the required standards. If it does not, remedial steps should be taken.

There is no standard form or system for recording field observations. The manner in which measurements are recorded depends in large part on the way they will be processed. Regardless of whether data will be recorded on paper forms or entered directly into electronic data recorders, consistent forms should be developed for recording information and made available to all crews. The forms should be developed such that they reflect the logical order of measurements and instructions to crews. Electronic data recorders can greatly speed up processing of forest inventory data since paper-based data do not have to be subsequently entered into a computer. Electronic data recorders should have internal data quality checks so that measurement or data entry errors can be identified and corrected in the field. Electronic data recorders often require more forethought in the design of data

entry forms since much field time can be lost if a user must scroll or page through several forms during field measurement procedures.

Plans for calculation and compilation of photo-interpretation data and field measurements should be made before fieldwork begins. It is illogical to postpone consideration of these things until data are obtained because foreknowledge of the calculation and compilation procedures can influence collection of data. For example, if volume tables will be used to determine tree volumes, there would be little point in measuring diameters to a tenth of a centimeter in the field if the volume tables give volumes by full centimeter dbh classes. The statistical formulas or computer programs to be used for estimating means, totals, and standard errors should be selected early in the planning process. It is worthwhile to check the formulas with simulated data to verify the applicability of the program or to work out the optimum sequence of computational steps.